

Galvanised basic fuel station

with winding reel



OPTION
EXTENDED WARRANTY FOR THE TANK
3-year - 5-year - 10-year

TANKS

TECHNICAL CHARACTERISTICS

HDPE fuel tank with metal reinforcements; meets the requirements of NF standards

Fuel pump 60L/min, 220 V, with:

8 m suction and discharge hoses

Automatic gun

Flowmeter with summer

Differential circuit breaker

Gauge

Filling plug

Diesel filter water settling tank

Cabinet:

Lock up your pumping equipment

Restrict access to authorised individuals

Galvanised retention tray with:

2 securing points

Padlock-compatible galvanised tipup cover

Galvanised base with fork slots

info

For fuel storage and fuel distribution, locking device

The small galvanised retention tray with its thickness of 3 mm protects the tank against any impact or vandalism. It can also be used to ensure compliance with standards on pollutant products

Reference	Capacity in Litres	L in mm	W in mm	H in mm
01020703005	1000	1200	810	1650
01020703006	1500	1750	830	1650
01020703007	2000	2200	850	1650
01020703008	2500	2350	1000	1500



DETAILS

- ① HDPE fuel tank with metal reinforcements
- ② 1 cabinet with lock, to secure pumping equipment
- ③ Padlock-compatible tipup cover
- ④ Base with fork slots
- ⑤ 8 m winding reel

ON-LINE QUOTES
www.beiser-se.com
AND PURCHASING



BEISER
environnement

sale of agricultural equipment by telephone

00 333 88 70 91 29