



Polyester silo

In kit form



Silo supplying a milking robot, by flexible grain auger



Unique on the market

AS STANDARD

- 4" fire hydrant
- Outlet offset by 15 cm with guillotine
- Flexible hose 1.50 m long for offset outlet
- Galvanised inspection hatch
- Anchorage kit for polyester silo

OFFSET OUTLET
with 1.50 m of pipe. Ideal for loading a bucket or other

INSPECTION HATCH
Unique on the market, makes regular cleaning of your silo easy with no complications

ADVANTAGES

- + Made of special glass fibre: considerable mechanical resistance and thermal insulation
- + Light, hermetic
- + Good ventilation, does not rust: long life
- + Inspection hatch
- + Offset outlet Ø 150 with 1.50 m of pipe

TECHNICAL SPECIFICATIONS

Reference	Capacity in m ³	Capacity in tonnes	Dimensions H x Ø in mm	Overall dimensions in m ²	Total weight in kg
03030100051	4	2.4	3870 x 1500	2.8	209
03030100052	6	3.6	4320 x 1900	2.8	254
03030100053	8	5.1	5080 x 2010	2.8	282
03030100054	10	6	5565 x 2055	3	326
03030100055	12	7.5	5650 x 2220	2.8	378
03030100056	15	8.4	6030 x 2320	3	439
03030100057	18	10.8	6680 x 2350	3	489
03030100058	20	12	7000 x 2500	3	558
03030100059	31	18.6	9025 x 2540	3	970



Offset cone



Drop-down gate

Various types of recovery:

- Auger or drop-down gate recovery
- Offset cone with 3 m of tube Ø 250

OPTIONS

Reference	Description
03039900002	Grain auger recovery
03039900003	Drop-down gate recovery
03039900008	Offset cone with 3 m of tube Ø 250
03039900006	Raised on 3 1-m feet for silo 3.5 to 15 m ³
03039900007	Raised on 4 1-m feet for silo 17.5 m ³

OPTIONS: INCLINED GRAIN AUGER

Reference	Dimensions Ø x W in mm	Output in HP
03040100010	100 x 3000	1.5
03040100011	100 x 4000	1.5
03040100012	100 x 5000	2
03040100015	120 x 3000	2
03040100016	120 x 4000	2
03040100017	120 x 5000	2
03040100020	150 x 3000	3
03040100021	150 x 4000	3
03040100022	150 x 5000	4